



Industrie Service

## Test report

**Choose certainty.  
Add value.**

Sound level measurements for the determination of sound power levels of Waste-Glass-Containers converted with „Anti-Noise-LärmDämmSystem“ according to RAL-UZ 21 (04/2003) in combination with Directive 2000/14/EC



DAP-PL-2885.99

Container type: **Waste-Glass-Container  
Euro Leader**

Client: **EHG Dienstleistungs GmbH  
Sondermoninger Straße 5  
83339 Chieming**

Date of order: **27.10.2007**

Order-Reference: **Herr Schimmelpfennig**

Test subject: **Noise level measurements**

Order-No.: **801395**

Report-No.: **F3/94**

Expert: **Dipl.-Ing. (FH) Herbert Leiker**

Telephone: **(0 89) 57 91-23 57**

Telefax: **(0 89) 57 91-11 74**

E-Mail: **[herbert.leiker@tuev-sued.de](mailto:herbert.leiker@tuev-sued.de)**

Date: 09.11.2007

Reference:  
IS-US6-MUC/lei

Document:  
Euro Leader english.doc

Report No. F3/094-LG

This document consists of  
1 pages und one page annex  
Page 1 of 1

Publishing excerpts of this  
document needs written permission  
of TÜV SÜD Industry Service  
GmbH.

The test results refer exclusively  
on the tested objects.

**The following results do not refer subject to noise marking for waste-glass-  
containers placed in the market according to directive 2000/14/EC**

## Measurement method according to para. 4 of RAL-UZ 21

Cycle: Throwing of 120 bottles into an empty container. Measurement for each bottle when being thrown into the container simultaneously at 6 microphone positions.

Quantity to be measured: Single-event sound pressure level  $L_{p1s}$

Target quantity: Sound power level  $L_{WAAd}$

**Guaranteed sound power level  $L_{WAAd} = \text{Measured sound power level } L_{WA} + \text{Measurement uncertainty } K$**

Number of tested containers of one type: 1

Resulting sound power levels:  $L_{WA} = 86,3 \text{ dB(A)}$

Statistical procedure for measurement uncertainty K: **Single measurement according to appendix of RAL-UZ 21**

Measurement uncertainty K:  **$K = 3 \text{ dB}$**

### Result:

Container Type	„Guaranteed“ Sound Power Level $L_{WAAd,SEL}$
Waste-Glass-Container Euro Leader	89

Munich, 08.11.2007  
TÜV SÜD Industrie Service GmbH  
Environmental Service  
Certified body according to DIN EN ISO/IEC 17025

Expert Noise/Vibration

gez. P. Thaler



Peter Thaler

Herbert Leiker

